
FAIRCHILD





GENERAL INFORMATION -

MODEL 25 REVERSING RELAY

APPLICATIONS

The Model 25 Reversing Relay provides an output which will decrease in direct proportion to an increase in input pressure.

FEATURES

Performance

- A Balanced Supply Valve minimizes the effects of supply pressure variation.
- Aspirator Tube minimizes downstream pressure droop under flowing conditions.

Functional

 Flow of up to 40 SCFM with 100 psig Supply allows use in applications requiring high flow capacity.

Physical

- A Separate Control Chamber isolates the diaphragm from the main flow, eliminating hunting and buzzing.
- Mounting Bracket available.

- NOTE: -

The information for this catalog sheet is being upgraded to electronic format and will be available soon. Please go to the Information Request section of this web site to order the latest printed revision.

— ORDERINGINFORMATION —

Catalog Number		2 5			
Pressure Range ———					
psig	[BAR]	(kPa)			
0-10	[0-0.7]	(0-70)	(42)		
0.5-30	[0.03-2]	(3-200)	(43)		
1-60	[0.1-4]	(10-400)	(44)		
2-150	[0.15-10]	(15-1000)	(46)		
Pipe Size					
1/4" NPT			(2)		
3/8" NPT				(3)	
1/2" NPT				(4)	
Options -					
Tapped Exhaust					(E)
BSPT (Tapered)					(U)
BSPP (Parallel) ¹					(H)

¹ BSPP Threads in Inlet & Outlet Ports Only. Others BSPT.





